

SHRINK TUNNEL

MODEL: SB3422



FEATURES

TUNNEL CHAMBER

- Digital Tunnel Temperature Control
- High Velocity Air Flow with Adjustable Side Air Manifolds
- Open Coil Heating Element Guaranteed for 10 Years
- Two Heat Zones
- High Temperature Limit Switch
- Automatic Cool Down Extends Heating Element Life


CONVEYOR FEATURES

- Intralox High Temperature Variable Speed Conveyor
- One Quarter Horsepower Motor With Adjustable Conveyor Speeds Of Up To 35 Feet Per Minute



Model SB3422 SWB

Side Air Manifolds shown on SB1311



OTHER FEATURES

- Heavy Gauge Adjustable Height Console With Levelers And 3" Casters
- Stainless Steel Model Available
- Two Year Warranty

MODEL SPECS

INSIDE TUNNEL DIMENSIONS	34" L, 22" W, 10" H (86 cm L, 56 cm W, 25 cm H)
CONVEYOR	Variable Speed, Intralox Belt
CONVEYOR SPEED	0 - 35 ft./min. (9 m./min.)
OVERALL DIMENSIONS	60" L, 31" W, 57" H (153 cm L, 79 cm W, 145 cm H)
POWER REQUIREMENTS	208~240 Volts, 9 Amps Single Phase
WATTAGE	2,200 Watts
WEIGHT	560 lbs. (255 kg)

AVAILABLE OPTIONS

- Stainless Steel Construction (SB3422S)
- Shrink Band Hold Down Kit
- 14" High Tunnel Opening
- Left Hand Reverse Flow

