

SHIPMATE SKIN PACKAGING SYSTEM by Ampak

MODEL: SP1824A, EZ-24, OF-24



Shipmate SP1824A with EZ-24 and OF-24 shown

This skin packaging system is made up of three components: an automatic infeed, the Shipmate skin packaging machine, and an automatic outfeed. For larger formats, the Master skin packaging machine is also available.

FEATURES

EZ INFEED

- Power and Controls from host skin machine
- Soft-Start Eliminates Product Movement
- Optional Stationary Template for Loading Accuracy and Speed

SHIPMATE SKIN PACKAGER

- PLC controls with Touch Screen Access
- Energy Saving Instant-On Spirad™ Oven
- Variable Speed Turbine Vacuum System

EZ OUTFEED

- Protective Covers for Operator Safety
- Virtually Maintenance Free Design

ROTOCUT DIE CUTTER

- Bi-Flex Cutting Principle (Cutting Force Concentrated Between 2 Pressure Rolls)
- Powered 6" Diameter Rigid Steel Pressure Rollers
- Heavy Duty Self Aligning Roller Bearings



Rotocut RC2400

SYSTEM SPECS

PLATEN SIZE	18" W, 24" L (46 W, 61 L cm)
MAX PRODUCT HEIGHT & WEIGHT	5" (12 cm) 20 lbs. (9 kg)
PLATEN HEIGHT	40" (102 cm)
FILM CAPACITY	20" W, 9" OD, 3" ID (51 W, 23 OD, 7.5 ID cm)
OVERALL DIMENSIONS	SP1824A: 43" W, 39" D, 60" H (109 W, 99 D, 152 H cm) EZ-24: 24 1/2", 56" (62 cm, 140 cm) OF-24: 34", 96 1/4" (85 cm, 241 cm)
POWER REQUIREMENTS	208 Volt, 41 Amps, Single Phase
AIR	2 cfm @ 80psi

ROTOCUT SPECS

CUTTING AREA	18" W, 24" L (46 W, 61 L cm)
OVERALL DIMENSIONS	43" W, 90" L, 53" H (109 W, 229 L, 135 H cm)
POWER REQUIREMENTS	115, 208, 230 Volt, Single Phase, 15 Amp

