

All Electric Automatic Side Sealer

MODEL: HDX 3000



FEATURES

- All Electric, No Air Required
- Interlocked Acrylic Guard Door w/ easy machine access
- Brushless Servo Motor Controlled Hot Knife Seal System
- Motorized Adjustment of Inverting Head and Seal Height
- Swing Arm Control panel
- Plug and Play Set Up
- 20-100 Feet/Min Conveyor Speeds, Variable Frequency AC Drive



OTHER FEATURES

- Motorized Movement of
 - Seal Opening
 - Seal Height
 - Inverting Triangle Height
- Adjustable Seal Force
- Closing Conveyor
- Seal Cooling for Polyethylene
- Extended Infeed and Outfeed Belts
- Powder Coated Steel Construction
- FDA Approved Belts
- Two Individually Adjustable Film Perforators
- Easy Thread Scrap Rewind w/ Scrap Break And Scrap Film Alarms
- Illuminated Work Area
- Casters and Leveling Pads
- Two Year Limited Warranty
- Simple Recipe Storage

MODEL SPECS

| | |
|---------------------------|---|
| SEAL AREA | 15.5" W, ∞" L (400mm W) |
| FILM CAPACITY | 27.5" W, 11.75"OD (700mm W, 300mm OD) |
| CONVEYOR SPEED | VARIABLE 20 – 100 FPM (6-30 mpm) |
| PRODUCTION RATE | 0 – 40 PPM, Dependent upon product and film size |
| MAXIMUM PRODUCT DIMENSION | ∞" L, 15.5" W, 9.25" H (∞" L, 400mmW, 240mmH) Maximum dimensions cannot be used simultaneously |
| POWER REQUIREMENTS | 208-240 VAC, SINGLE PHASE, 10.5A |
| CONVEYOR HEIGHT | 34.8" (880mm) |
| OVERALL DIMENSIONS | 100" L, 49" W, 62" H (2518mm L, 1240mm W, 1558mm H) |
| WEIGHT | 1940 Lbs. (880) Kg) |

AVAILABLE ACCESSORY OPTIONS

- Infeed and Outfeed Conveyors
- Printer
- Photocell Kit for Printed Film
- Electric Film Hole Punch
- Irregular Shape Product Photo Cell Kit (5pc)
- Product Guides for Unstable Products



9/19/2024